

# EP Power Grit

## Product Data Sheet

# ASILROOF

**ASILROOF** is a synthetic, mineral, environment-friendly granular cover material on the basis of aluminium silicate glass melt, with the following technical details:

### CHEMICAL ANALYSIS

Aluminium silicate glass melt;  
chemical composition calculated as oxides:

Silicon dioxide	42 – 58 %
Aluminium oxide	23 – 32 %
Iron (III) oxide	3 – 15 %
Calcium oxide	2 – 8.5 %
Potassium oxide	0.5 – 4.6 %

The metals present are chemically bound in the form of silicates or aluminates.

### CONTAINS NO WATER-SOLUBLE CONSTITUENTS

### CONTAINS NO FREE CRYSTALLINE SILICIC ACID

Specific weight/ grain density	2.4 – 2.6 kg/dm <sup>3</sup>
Bulk density, for standard grain sizes	1.05 – 1.4 kg/dm <sup>3</sup>
Mohs hardness	min. 7

### USE

- Granular cover material

### FIELDS OF APPLICATION

- Bitumen roofing

### GRAIN SIZES

- on request

### PACKING

- 1,000 kg/ 1,350 kg big bags
- in bulk

August 2023

**EP Power Grit GmbH**  
Duisburger Str. 170  
46535 Dinslaken, Germany  
E-Mail: [info@epowergrit.com](mailto:info@epowergrit.com)

